



MODELS
X2K7
X3K5
X5K5

X2K7			
Motor Mount:	SAE "CC" 4 Bolt		
Motor:	315.0cc Bi - Directional Speed		
Min. Hydraulic Flow:	10 GPM (US)		
Max. Hydraulic Flow:	35 GPM (US)		
Max. Continuous Pressure:	3000 psi		
Output Shaft:	2" Hex		
Output Speed		Output Torque	
Flow GPM (US)	Speed RPM	Pressure PSI	Torque FT/LBS
10	23	1000	904
15	35	1500	1357
25	59	2250	2035
35	82	3000	2713

X3K5			
Motor Mount:	SAE "CC" 4 Bolt		
Motor:	315.0cc		
Min. Hydraulic Flow:	10 GPM (US)		
Max. Hydraulic Flow:	35 GPM (US)		
Max. Continuous Pressure:	3000 psi		
Output Shaft:	2" Hex		
Output Speed		Output Torque	
Flow GPM (US)	Speed RPM	Pressure PSI	Torque FT/LBS
10	19	1000	1134
15	28	1500	1701
25	47	2250	2552
35	66	3000	3403

X5K5			
Motor Mount:	SAE "CC" 4 Bolt		
Motor:	500.0cc Bi - Directional Speed		
Min. Hydraulic Flow:	10 GPM (US)		
Max. Hydraulic Flow:	40 GPM (US)		
Max. Continuous Pressure:	3000 psi		
Output Shaft:	2" Hex		
Output Speed		Output Torque	
Flow GPM (US)	Speed RPM	Pressure PSI	Torque FT/LBS
10	12	1000	1848
20	24	1500	2771
30	36	2250	4157
40	48	3000	5543

MODELS X2K7, X3K5, X5K5

